



**GENUINE. PROFESSIONAL.**





## POWERFUL, PRACTICAL AND PRODUCTIVE.

Snapper Pro® Mowers are where innovation meets common sense practicality to keep you mowing season after season. With powerful engine choices, heavy-duty components and technology, like the iCD™ Cutting System, Snapper Pro mowers are the smart choice for your landscaping needs.

**iCD™ CUTTING SYSTEM** .....3

### ZERO-TURN MOWERS

**S800x**.....5

**S200xt**.....7

**S150xt**.....9

**S125xt**.....11

**S50xt**.....13

### WALK-BEHIND MOWERS

**SW35** .....15

**SW25** .....17

**COLLECTION SYSTEMS** .....19

**ACCESSORIES & ATTACHMENTS**...23

**MODEL SELECTION CHART** .....24

**SPECIFICATIONS** .....25







# iCD™ CUTTING SYSTEM

## IT'S ALL ABOUT THE CUT

The iCD™ Cutting System was engineered to produce the best possible cut in a multitude of conditions. Every component works together to achieve superior cut quality. The deck design and extra wide discharge opening allow for a more even and greater dispersal of clippings. The shell features a sloped nose design which allows the blades of grass to rise in the chamber before making contact with the blades and also reduces the amount of clippings that are discharged from the front. Slice through thick grass with ease and get the job done sooner than you expected.



Snapper Pro® uses two layers of steel, running across the full width of our deck, welded in opposing directions, for maximum strength. Then we lap-weld the corners for increased dent resistance.

1. Flexible recycled rubber discharge chute reduces contact damage
2. Extra wide discharge opening evenly disperses grass clippings
3. Reinforced leading edge provides protection where the deck needs it most
4. Multi-layer heavy-gauge steel construction for maximum strength
5. Debris shield on idler pulleys keeps moisture and debris away extending bearing life
6. Center point is offset, optimizing airflow for discharge
7. Slope nose design reduces the amount of clippings discharged from the front
8. Deck step allows for easy entry and exit from the operator's compartment




**HERCULES™ II SPINDLES**  
Industrial 10" dia. cast-iron spindle assembly with 1 3/16" dia. shaft and greaseable double row angular contact ball bearings, which can be greased through the convenient top access grease fitting.



**CAST-IRON SPINDLES**  
Longer usable life, 1" shaft with top access grease fitting for greaseable dual ball bearings, six-bolt 8" flange design adds strength and greater dispersal of energy to deck assembly.



**CAST-ALUMINUM SPINDLES**  
Feature 1" shaft with greaseable 2.5" x 1" dual ball bearings with top access grease fittings and pressure relief valve.



**MARBAIN® STEEL BLADES**  
Our exceptionally strong 1/4" thick blades generate greater lift for a precision cut and require less frequent sharpening.



**PROFESSIONAL LAWN STRIPER**  
Standard equipment on all iCD™ Cutting System decks.



# S800X

## PROFESSIONAL



The S800x zero-turn mower is the ideal machine for visibility and versatility. Its out-front design is perfect for trimming around trees, bushes and landscaped areas with ease. Be even more productive with a wide selection of accessory and attachment options.



Raise the deck with a flip-of-the-switch to make deck maintenance a snap.



Electric deck lift makes for easy cut-height adjustment.



Optional 60" broom clears debris and snow right down to the pavement. (Optional cab not shown.)



The pivoting rear axle in conjunction with the floating front frame allows the S800x to follow the contours of the landscape for a precise, manicured finish.

MOWS UP TO  
**5.8 ACRES/HOUR**  
BASED ON 80% EFFICIENCY

**MODEL**  
S800XBV31 w/S800X/61  
S800XBV31 w/S800X/72

**ENGINE** (Gross Horsepower/Displacement)  
Vanguard™ (31\*/896cc)  
Vanguard™ (31\*/896cc)

**DECK**  
61"  
72"

\* All power levels are stated gross horsepower at 3600 RPM per SAE J1940 as rated by Briggs & Stratton.

## VISIBILITY & VERSATILITY

### ENGINE

- Vanguard™ Engine
- Two-stage industrial air cleaner extends engine service life
- Easy access oil drain

### DRIVE SYSTEM

- Independent pumps and wheel motors, feature 7" cooling fans that assist with repelling debris
- Hydro fluid reservoir and hydro filter
- Rugged 5/8" hoses supply a constant flow of fluid cooling the hydro system
- Ground speed up to 10 mph

### MOWER DECK

- Available in 61" or 72" cutting widths
- iCD™ Cutting System with professional lawn striper
- Cast-iron spindles with greaseable bearings for longer usable life, 1" shaft with top access grease fitting, 6-bolt 8" flange design adds strength and greater dispersal of energy to deck assembly
- Electric deck-lift makes for easy cut height adjustment; cutting height ranges from 1.5" - 5" in 0.25" increments
- Debris shields on idler pulleys extend bearing life

### CHASSIS

- Heavy-duty C-channel, 7-gauge frame rails
- Flip-up seat for easy access

### FUEL SYSTEM

- Twin 6-gallon rugged, impact resistant fuel tanks with extra large filler necks
- Switch for fuel source
- Top-mounted fuel pick-up with Viton® Seals

### OPERATOR CONVENIENCE

- Premium mid-back adjustable seat with padded arm rests
- Ergonomic control panels with cup-holder and storage compartment
- Adjustable solid steel padded control arms

### ACCESSORIES

- Collection system (61"), mulch kit, suspension seat, suspension seat insert, flat-free caster tires, snowblower/cab, broom/cab





# S200xt

## PROFESSIONAL



Vanguard™ 810 EFI Engines deliver more grass cutting capability than the leading EFI engine. Up to 25% fuel savings!



Dual, commercial Hydro-Gear® ZT-5400 Powertrain® Transaxles deliver unmatched power and durability.



The easy-to-use deck-lift takes the effort out of adjusting cut height. Cutting height ranges from 1.5" - 6" in 0.25" increments.



Quick removal of the floor pan provides convenient access to the top of the deck for easy cleaning and service.

### ENGINE

- Choose from Kawasaki® FX801V, Vanguard™ 810, Briggs & Stratton® Commercial Series, Vanguard™ 810 EFI, Vanguard™ BIG BLOCK™, or Vanguard™ BIG BLOCK™ EFI Engine options
- Patented advanced debris management system (Briggs & Stratton® Commercial Series Models)
- Two-stage industrial air-cleaner (Vanguard™ and Kawasaki® Models)
- Easy access oil drain

### DRIVE SYSTEM

- Independent, commercial Hydro-Gear® ZT-5400 Powertrain® Transaxles feature 9" cooling fans that assist with repelling debris
- Dual hydro fluid reservoirs and hydro filters
- Pneumatic caster tires
- Five-bolt pattern wheels, 1/4" solid center wheels
- Ground speed up to 10 mph

### MOWER DECK

- Available in 61" or 72" cutting widths
- iCD™ Cutting System with professional lawn striper
- Cast-iron spindles with greaseable bearings for longer usable life, 1" shaft with top access grease fitting, 6-bolt 8" flange design adds strength and greater dispersal of energy to deck assembly (61" models)
- Hercules™ II Spindles; 10" dia. cast-iron with industrial double row angular contact ball bearings with 1 3/16" dia. shaft (72" model)
- Cut height: 1.5" - 6", adjust in 0.25" increments
- Debris shields on idler pulleys extend bearing life

### CHASSIS

- Heavy-duty 2" x 2" 7-gauge frame rails
- Removable floor pan
- Heavy-duty bumper protects engine compartment

### FUEL SYSTEM

- Twin 5-gallon rugged, impact resistant fuel tanks with switch for fuel source (excludes S200XTB2761)
- Single 5-gallon rugged, impact resistant fuel tank (S200XTB2761)
- Extra large filler neck(s)
- Top-mounted fuel pick-up with Viton® Seals

### OPERATOR CONVENIENCE

- Premium mid-back adjustable seat with padded arm rests
- Flip-up seat for easy access
- Ergonomic control panels with cup-holder and storage compartment
- Adjustable solid steel padded control arms

### ACCESSORIES

- Collection system (61"), mulch kit, trailer hitch kit, light kit, suspension seat, flat-free caster tires

# PRODUCTIVITY REDEFINED

The S200xt is equipped to ride for a full day of work with impressive features and premium components. Available with our iCD™ Cutting System deck in 61" and 72" cutting widths, the S200xt will cut your big jobs down to size. This machine delivers maximum performance and productivity.



MOWS UP TO  
**5.8 ACRES/HOUR**  
BASED ON 80% EFFICIENCY

MODEL	ENGINE (Gross Horsepower/Displacement)	DECK
S200XTKAV2661	Kawasaki® FX801V (25.5*/852cc)	61"
S200XTBV2661	Vanguard™ 810 (26**/810cc)	61"
S200XTB2761	Briggs & Stratton® Commercial Series (27**/810cc)	61"
S200XTBVE2861	Vanguard™ 810 EFI (28**/810cc)	61"
S200XTBV2861	Vanguard™ BIG BLOCK™ (28**/896cc)	61"
S200XTBVE3761	Vanguard™ BIG BLOCK™ EFI (37**/993cc)	61"
S200XTBVE3772	Vanguard™ BIG BLOCK™ EFI (37**/993cc)	72"

\* All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki.  
\*\* All power levels are stated gross horsepower at 3600 RPM per SAE J1940 as rated by Briggs & Stratton.



# S150xt

## PROFESSIONAL

This compact yet powerful performer is designed for the serious professional who demands the ultimate in performance and durability. Get in and out of your jobs fast with the S150xt zero-turn mower.

### ENGINE

- Choose from Kawasaki® FX730V , or Vanguard™ 810 EFI Engine options
- Two-stage industrial air-cleaner
- Easy access oil drain

### DRIVE SYSTEM

- Independent, commercial Hydro-Gear® ZT-4400 Transaxles feature 8.3" cooling fans that assist with repelling debris
- Dual hydro fluid reservoirs and hydro filters
- Five-bolt pattern wheels
- 24" drive tires and pneumatic caster tires
- Ground speed up to 10 mph

### MOWER DECK

- Available in 48" or 52" cutting widths
- iCD™ Cutting System with professional lawn striper
- Cast-iron spindles with greaseable bearings for longer usable life, 1" shaft with top access grease fitting, 6-bolt 8" flange design adds strength and greater dispersal of energy to deck assembly (52" model)
- Features cast aluminum spindles with greaseable 2.5" diameter ball bearings (48" model)
- Cut height: 1.5" - 5", adjusts in 0.25" increments
- Debris shields on idler pulleys extend bearing life

### CHASSIS

- Heavy-duty 1.5" x 2" 11-gauge frame rails
- Removable floor pan
- Heavy-duty bumper protects engine compartment

### FUEL SYSTEM

- Twin 5-gallon rugged, impact resistant fuel tanks with switch for fuel source
- Extra large filler necks
- Top-mounted fuel pick-up with Viton® Seals

### OPERATOR CONVENIENCE

- Premium mid-back adjustable seat with padded arm rests
- Flip-up seat for easy access
- Ergonomic control panels with cup-holder and storage compartment
- Adjustable solid steel padded control arms

### ACCESSORIES

- Collection system, mulch kit, trailer hitch kit, light kit, suspension seat, flat-free caster tires



Dual, commercial Hydro-Gear® ZT-4400 Transaxles deliver unmatched power and durability.



Quick removal of the floor pan provides convenient access to the top of the deck for easy cleaning and service.



Vanguard™ 810 EFI Engines deliver more grass cutting capability than the leading EFI engine. Up to 25% fuel savings!



Cast-iron greaseable spindles maximize usable life. (52" model)



## A POWERFUL CHOICE

MOWS UP TO  
**4.2 ACRES/HOUR**  
BASED ON 80% EFFICIENCY

**MODEL**  
S150XTKAV2448  
S150XTKAV2452  
S150XTBVE2852

**ENGINE (Gross Horsepower/Displacement)**  
Kawasaki® FX730V (23.5\*/726cc)  
Kawasaki® FX730V (23.5\*/726cc)  
Vanguard™ 810 EFI (28\*\*/810cc)

**DECK**  
48"  
52"  
52"

\* All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki.  
\*\* All power levels are stated gross horsepower at 3600 RPM per SAE J1940 as rated by Briggs & Stratton.





# S125xt PROFESSIONAL



The easy-to-use deck-lift takes the effort out of adjusting cut height. Cutting height ranges from 1.5" - 5" in 0.25" increments.



Hydro-Gear® ZT-3400® Commercial Engineered Drive System is designed for high performance and is fully serviceable.



Quick removal of the floor pan provides convenient access to the top of the deck for easy cleaning and service.



The Briggs & Stratton® Commercial Series Engine features a patented advanced debris management system which deflects dirt and debris from the engine, and any remaining debris is trapped in the high-capacity, dual-sealing air cleaner cartridge.

## ENGINE

- Choose from Kawasaki® FS, Kawasaki® FS EFI or Briggs & Stratton® Commercial Series Engine options
- Patented advanced debris management system (Briggs & Stratton® Commercial Series Models)
- Easy-to-use oil drain

## DRIVE SYSTEM

- Independent, commercial Hydro-Gear® ZT-3400® Transaxles feature 7" cooling fans that assist with repelling debris
- Pneumatic caster tires
- Ground speed up to 10 mph

## MOWER DECK

- Available in 52" or 61" cutting widths
- iCD™ Cutting System with professional lawn striper
- Features cast aluminum spindles with greaseable 2.5" diameter ball bearings
- Cut height: 1.5"- 5", adjusts in 0.25" increments
- Debris shields on idler pulleys extend bearing life

## CHASSIS

- Heavy-duty 1.5" x 2" 11-gauge frame rails
- Removable floor pan
- Heavy-duty bumper protects engine compartment

## FUEL SYSTEM

- Single 5.5-gallon rugged, impact resistant fuel tank
- Extra large filler neck
- Top-mounted fuel pick-up with Viton® Seals

## OPERATOR CONVENIENCE

- Mid-back seat with arm rests
- Flip-up seat for easy access
- Ergonomic control panels with cup-holder and storage compartment
- Adjustable solid steel padded control arms
- Control system provides smooth precise steering

## ACCESSORIES

- Collection system, mulch kit, trailer hitch kit, light kit, premium mid-back seat, flat-free caster tires

MOWS UP TO  
**4.9 ACRES/HOUR**  
BASED ON 80% EFFICIENCY

## MODEL

S125XTKAV2352  
S125XTB2552  
S125XTKAV2461  
S125XTKAVE2661  
S125XTB2761

## ENGINE (Gross Horsepower/Displacement)

Kawasaki® FS691V (23\*/726cc)  
Briggs & Stratton® Commercial Series (25\*\*/724cc)  
Kawasaki® FS730V (24\*/726cc)  
Kawasaki® FS730V EFI (25.5\*/726cc)  
Briggs & Stratton® Commercial Series (27\*\*/810cc)

## DECK

52"  
52"  
61"  
61"  
61"

\* All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki.  
\*\* All power levels are stated gross horsepower at 3600 RPM per SAE J1940 as rated by Briggs & Stratton.

# VALUE & PERFORMANCE

With powerful engine choices, 52" or 61" iCD™ Cutting System options and speed up to 10 mph, the S125xt zero-turn mower will cut your job down to size. The heavy-duty components, including the commercial Hydro-Gear® ZT-3400® Transaxles, will keep you mowing season after season.





# S50xt

## PROFESSIONAL



The compact, easy-to-use S50xt zero-turn mower is designed specifically for the daily rigors of commercial mowing. This mower may be small in size, but it's big on features.

# COMPACT & TOUGH

MOWS UP TO  
**3.1 ACRES/HOUR**  
BASED ON 80% EFFICIENCY

MODEL	ENGINE (Gross Horsepower/Displacement)	DECK
S50XTKAV1936	Kawasaki® FX600V (19"/603cc)	36"
S50XTB2536	Briggs & Stratton® Commercial Series (25"/724cc)	36"
S50XTKAV1948	Kawasaki® FX600V (19"/603cc)	48"
S50XTB2548	Briggs & Stratton® Commercial Series (25"/724cc)	48"

\* All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki.  
\*\* All power levels are stated gross horsepower at 3600 RPM per SAE J1940 as rated by Briggs & Stratton.

### ENGINE

- Choose from Kawasaki® FX600V or Briggs & Stratton® Commercial Series Engine options
- Patented advanced debris management system (Briggs & Stratton® Commercial Series Models).
- Two-stage industrial remote air-cleaner (Kawasaki® models)
- Easy access oil drain

### DRIVE SYSTEM

- Independent, commercial Hydro-Gear® ZT-3100® Transaxles feature 7" cooling fans that assist with repelling debris
- Dual hydro fluid reservoirs and hydro filters
- Pneumatic caster tires
- Ground speed up to 8 mph

### MOWER DECK

- Available in 36" or 48" cutting widths
- iCD™ Cutting System with professional lawn striper on 48" models
- Fabricated 10-gauge with double top deck, overlap welded corners and double reinforced side skirts, steel reinforced leading edge on 36" models
- Cast-aluminum spindles feature 1" shaft with greaseable 2.5" x 1" dual ball bearings with top access grease fittings and pressure relief valve
- Durable, .25" Marbain® Steel blades
- Cut height: 1.5" - 4.5", adjusts in 0.25" increments
- Debris shields on idler pulleys extend bearing life

### CHASSIS

- Heavy-duty 1.5" x 2", 11-gauge frame rails
- Adjustable contour seat
- Removable floor pan
- Heavy-duty bumper protects engine compartment

### FUEL SYSTEM

- Twin 4-gallon rugged, impact resistant fuel tanks with switch for fuel source (excludes S50XTB2536)
- Single 4-gallon rugged, impact resistant fuel tank (S50XTB2536)
- Extra large filler neck(s)
- Top mounted fuel pick-up with Viton® Seals

### OPERATOR CONVENIENCE

- Flip-up seat for easy access
- Ergonomic control panels
- Adjustable solid steel padded control arms

### ACCESSORIES

- Collection system (48"), grass catcher (36"), mulch kit, trailer hitch kit, light kit, armrests, flat-free caster tires, professional lawn striper (36")



The easy-to-use deck-lift takes the effort out of adjusting cut height. Cutting height ranges from 1.5" - 4.5" in 0.25" increments.



Features greaseable cast-aluminum spindles for longer usable life.



Quick removal of the floor pan provides convenient access to the top of the deck for easy cleaning and service.



Hydro-Gear® ZT-3100® Drive System is designed for high performance and is fully serviceable.







SW35 shown with standard controls.

# SW35 PROFESSIONAL

The SW35 delivers consistently accurate cutting performance in diverse conditions. Built to run sunrise to sundown, this walk-behind is a productive performer for any size mowing crew.



Robust 1/4" steel engine deck construction provides mounting area for sulky attachments.



Deck drive belt system is designed to provide even belt tension which improves the life of the belt and reduces maintenance.



Reliably set your speed with the improved easy-to-reach cruise control bar featuring a speed indicator. Conveniently located brake handle.



Set cutting height in one easy step using the quick-adjust crank.

## ENGINE

- Powerful Kawasaki® FX Engines
- Electric start standard
- Two-stage industrial remote air-cleaner
- Easy-to-use oil drain

## DRIVE SYSTEM

- Independent, commercial Hydro-Gear® ZT-3100® Transaxles feature 7" cooling fans that assist with repelling debris
- Dual hydro fluid reservoirs and hydro filters
- Narrow transmission guards reduce build up of debris to improve air flow and allow for access to the filter for maintenance
- Flat-free caster tires
- Ground speed up to 7 mph

## MOWER DECK

- New larger discharge opening on 52" and 61" decks for improved displacement of grass clippings
- Available in 48", 52", or 61" cutting widths
- Fabricated 10-gauge with double top deck, overlap welded corners and double reinforced side skirts, steel reinforced leading edge
- Cast-aluminum spindles feature 1" shaft with greaseable 2.5" x 1" dual ball bearings with top access grease fittings and pressure relief valve
- The mower deck mounting system provides easier deck leveling, improved flexibility over terrain, and more durable wear points for reduced maintenance
- Cut height: 1.5" - 4.75", with infinite positioning using the quick-adjust crank
- Debris shields on idler pulleys extend bearing life

## CHASSIS

- Heavy-duty 1.5" x 2" 11-gauge frame rails
- Easy to access dump valves
- Dedicated tie-down points, located in the front and rear, makes securing equipment convenient

## CONTROLS

- CC™ Centralized Controls or standard control options available

## FUEL SYSTEM

- Rugged 5-gallon fuel tank
- Top-mounted fuel pick-up with Viton® Seals

## OPERATOR CONVENIENCE

- Centralized foot control for neutral position
- Easy-to-reach cruise control bar
- Comfortable easy-to-use operator controls
- Momentary PTO switch allows the operator to stop the mower blades while the engine continues to run. Simply put the machine in neutral and release the controls

## ACCESSORIES

- Grass catcher (48", 52"), mulch kit, professional lawn striper

MOWS UP TO  
**3.5 ACRES/HOUR**  
BASED ON 80% EFFICIENCY

## MODEL

- SW35KAV2148
- SW35KAV2152
- SW35KAV2461
- SW35CCKAV2148
- SW35CCKAV2152
- SW35CCKAV2461

## ENGINE (Gross Horsepower/Displacement)

- Kawasaki® FX651V (20.5"/726cc)
- Kawasaki® FX651V (20.5"/726cc)
- Kawasaki® FX730V (23.5"/726cc)
- Kawasaki® FX651V (20.5"/726cc)
- Kawasaki® FX651V (20.5"/726cc)
- Kawasaki® FX730V (23.5"/726cc)

## CONTROLS DECK

- | CONTROLS | DECK |
|----------|------|
| Standard | 48"  |
| Standard | 52"  |
| Standard | 61"  |
| CC™      | 48"  |
| CC™      | 52"  |
| CC™      | 61"  |

\* All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki.

# SMOOTH OPERATORS

The design of the CC™ Centralized Controls places the operator's hands in the ideal position to access all in-demand controls. Ergonomic operator presence, steering and reverse levers on both handles operate with a light touch to reduce operator fatigue.





SW25 shown with CC™ controls.



# SW25

## PROFESSIONAL

Snapper Pro® Walk-Behind Mowers will keep you mowing even under the most demanding conditions. Whether shuttling between jobs or maneuvering around obstacles, this walk-behind is a heavy-duty performer in an efficient package.

# COMPACT PERFORMANCE

MOWS UP TO  
**2.4 ACRES/HOUR**  
BASED ON 80% EFFICIENCY

MODEL	ENGINE (Gross Horsepower/Displacement)	CONTROLS	DECK
SW25KAV1536	Kawasaki® FS541V Manual Start (15*/603cc)	Standard	36"
SW25KAV1548	Kawasaki® FS541V Manual Start (15*/603cc)	Standard	48"
SW25KAV1948	Kawasaki® FS600V Electric Start (18.5*/603cc)	Standard	48"
SW25CCKAV1936	Kawasaki® FS600V Electric Start (18.5*/603cc)	CC™	36"
SW25CCKAV1548	Kawasaki® FS541V Manual Start (15*/603cc)	CC™	48"
SW25CCKAV1948	Kawasaki® FS600V Electric Start (18.5*/603cc)	CC™	48"

\* All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki.

### ENGINE

- Powered by Kawasaki® FS Engine options
- Electric and manual start available

### DRIVE SYSTEM

- Independent, commercial Hydro-Gear® ZT-3100® Transaxles feature 7" cooling fans that assist with repelling debris
- Dual hydro fluid reservoirs and hydro filters
- Heavy-duty transmission guards reduce build up of debris to improve air flow and allow for access to the filter for maintenance
- Flat-free caster tires, wheels have cage bearings
- Ground speed up to 6 mph

### MOWER DECK

- Available in 36" or 48" cutting widths
- Fabricated 10-gauge with double top deck, overlap welded corners and double reinforced side skirts, steel reinforced leading edge
- Cast-aluminum spindles
- Cut height: 1.5"- 4.5", finite adjustment using pin style height of cut
- Debris shields on idler pulleys extend bearing life

### CHASSIS

- Heavy-duty 1.5" x 2" 11-gauge frame rails, one piece frame
- Dedicated tie-down points, located in the front and rear, makes securing equipment convenient
- 20 x 7-10 drive tires

### CONTROLS

- CC™ Centralized Controls or standard control options available

### FUEL SYSTEM

- Rugged 5-gallon fuel tank
- Top-mounted fuel pick-up with Viton® seals

### OPERATOR CONVENIENCE

- Centralized foot control for neutral position
- Easy-to-reach cruise control bar
- Comfortable easy-to-use operator controls
- Momentary PTO switch allows the operator to stop the mower blades while the engine continues to run. Simply step on the foot pedal or pull the Cruise Control bar and release the controls

### ACCESSORIES

- Grass catcher, mulch kit, professional lawn striper (48"), weight kit



Adjust the mower's speed without removing your hands from the control handles with the improved, ready-access cruise control bar. A convenient speed indicator is placed within direct view on the control panel.



Brake handle is conveniently located beside the control panel, providing instant access with minimal operator effort to engage.



New centralized foot pedal for neutral position provides the operator with more natural control. The neutral position is identified on the speed indicator on the dash.



Need to walk away from the mower to move an obstacle or debris? The new PTO switch allows the operator to stop the mower blades in a single step – simply put the machine in neutral and release the controls. The blades will disengage while the engine continues to run.

SW25 shown with standard controls.





# COLLECTION SYSTEMS

## TURBO-PRO™

The TURBO-Pro™ System makes collecting leaves and debris a breeze. This lightweight blower assembly is ideal for use with compact models. **Can be used in conjunction with the double bag soft / hard top, triple bag soft / hard top and DFS (Dump from Seat) bagging options.**

- Performs best in normal-to-dry cutting conditions
- Generous 6" diameter outlet hose
- Lightweight design built to withstand commercial use
- Durable plastic impeller housing
- Heavy-duty oversized drive and idler pulleys combined with long drive belt allow for cool running and maximum belt life
- Curved steel blade impeller reduces noise
- After initial installation, the quick attach design can be mounted or removed with no tools in a few minutes
- Approximate blower weight: 50 lbs. (44"/48") / 53 lbs. (52") / 55 lbs. (61"), includes mounting bracket



S125xt shown with a TURBO-Pro triple bag collection system.  
TURBO-Pro Blower — Length: 31" Height: 16.5" Width 19"

## TURBO-PRO™ MAX

The TURBO-Pro™ Max System acts as a lawn vacuum for a clean finish in a wide variety of conditions. This commercial-grade system mounts to the deck with a fabricated heavy-duty steel plate and is ideal for use with larger models. **Can be used in conjunction with the triple bag soft / hard top, DFS (Dump from Seat), EZ Dump™ or EZ Dump XL™ bagging options.**

- Performs best in normal-to-dry cutting conditions
- Extra wide 7" diameter outlet hose
- Twice the airflow vs. Turbo-Pro™ for increased capacity on larger decks cutting at higher speeds
- Rugged steel impeller housing designed for extended life
- Heavy-duty oversized drive and idler pulleys combined with a long drive belt allow for cool running and maximum belt life.
- After initial installation, the quick attach design can be mounted or removed with no tools in a few minutes
- Approximate blower weight: 72 lbs. (52") / 64 lbs. (61"), includes mounting bracket



S200xt shown with a TURBO-Pro Max EZ Dump XL collection system.  
TURBO-Pro Max Blower — Length: 36" Height: 18" Width 21"



# COLLECTION SYSTEMS

## FAST-VAC®

The FAST-Vac® System is built around a tough, high-volume side panel air induction system that reduces clogging and produces significantly more air volume than conventional systems. The rugged impeller utilizes industrial-grade bearings, generates phenomenal airflow. Its spindle-driven vertical turbo is narrower, allowing you to get in and out of tight places. **Can be used in conjunction with the triple bag soft / hard top, DFS (Dump from Seat), EZ Dump™ or EZ Dump XL™ bagging options.**

- Your optimal choice, especially in heavy and wet cutting conditions
- Super rugged impeller rides on industrial-grade bearings to generate a phenomenal airflow
- Commercial-grade idler and pulleys drive the vertical, spindle-driven turbo resulting in a very narrow profile for improved maneuverability
- Extra wide 7" diameter outlet hose
- Approximate blower weight: 83 lbs. (52") / 85 lbs. (61"), includes mounting bracket



S200xt shown with a FAST-Vac triple bag collection system.  
FAST-Vac Blower — Length: 36.8" Height: 20.2" Width 15.2"

S800X S200xt S150xt S125xt S50xt

	<b>DOUBLE BAG SOFT TOP</b> The double bag collection system is simple to install. Each heavy-duty mesh bag has a rugged polyethylene underside with integrated handle to assist with removal. Capacity: 8.5 cubic feet			TURBO-PRO™ 48/52" Deck	TURBO-PRO™ 52" Deck	TURBO-PRO™ 48" Deck
	<b>DOUBLE BAG HARD TOP</b> Innovative molded hard top design allows for increased capacity. Simple to install. Each heavy-duty mesh bag has an integrated handle to assist with removal. Capacity: 10 cubic feet			TURBO-PRO™ 48/52" Deck	TURBO-PRO™ 52" Deck	TURBO-PRO™ 48" Deck
	<b>TRIPLE BAG SOFT TOP</b> Simple to install. Each heavy-duty mesh bag has a rugged polyethylene underside with integrated handle to assist with removal. Capacity: 13 cubic feet		TURBO-PRO™ MAX 61" Deck FAST-VAC® 61" Deck	TURBO-PRO™ 52" Deck TURBO-PRO™ MAX 52" Deck FAST-VAC® 52" Deck	TURBO-PRO™ 52"/61" Deck FAST-VAC® 52"/61" Deck	
	<b>TRIPLE BAG HARD TOP</b> Innovative molded hard top design allows for increased capacity. Simple to install. Each heavy-duty mesh bag has an integrated handle to assist with removal. Capacity: 15 cubic feet		TURBO-PRO™ MAX 61" Deck FAST-VAC® 61" Deck	TURBO-PRO™ 52" Deck TURBO-PRO™ MAX 52" Deck FAST-VAC® 52" Deck	TURBO-PRO™ 52"/61" Deck FAST-VAC® 52"/61" Deck	
	<b>ELECTRIC DFS (Dump From Seat)</b> Simply flip the switch on the control panel to release the hopper right from your seat. Capacity: 13 cubic feet		TURBO-PRO™ MAX 61" Deck FAST-VAC® 61" Deck	TURBO-PRO™ 52" Deck TURBO-PRO™ MAX 52" Deck FAST-VAC® 52" Deck	TURBO-PRO™ 52"/61" Deck FAST-VAC® 52"/61" Deck	
	<b>EZ DUMP™ (Dump From Seat)</b> Simply squeeze the handle and pull up to release the hopper right from your seat. The hopper is specially lined to ensure that all material is dumped. Capacity: 12 cubic feet		TURBO-PRO™ MAX 61" Deck FAST-VAC® 61" Deck	TURBO-PRO™ MAX 52" Deck FAST-VAC® 52" Deck		
	<b>EZ DUMP XL™ (Dump From Seat)</b> Ideal for larger jobs. Simply squeeze the handle and pull up to release the hopper right from your seat. The hopper is specially lined to ensure that all material is dumped. Capacity: 14 cubic feet	TURBO-PRO™ MAX 61" Deck FAST-VAC® 61" Deck	TURBO-PRO™ MAX 61" Deck FAST-VAC® 61" Deck			



# ACCESSORIES & ATTACHMENTS



## MULCH KIT

Select kits include dedicated mulching blades, baffles, hardware and instruction sheet.



## TRAILER HITCH KIT

Will accept a 1/2" shank ball and comes complete with hardware.



## LIGHT KIT

Select zero-turn models are pre-wired for simple installation.



## LED LIGHT KIT

Energy efficient LED light kit with simple installation.



## ARMRESTS

Add these foldable armrests for increased riding comfort on S50xt.



## SUSPENSION SEAT INSERT

Add this to the premium seat on the S800x for increased comfort.



## SUSPENSION SEAT

Suspension seat for optimal comfort available on S800x, S200xt, and S150xt.



## PREMIUM SEAT

High quality adjustable seat features red trim with foldable padded armrests for added comfort. Optional on S125xt.



## FLAT-FREE CASTER TIRES

Run all day with no flats, eliminates downtime. Standard on walk-behind models.



## PROFESSIONAL STRIPE KIT

Rubber flap system lays down grass to create patterns across the landscape. Standard on iCD™ Cutting System decks.



## SNOWBLOWER/CAB

Two-stage 60" snowblower and cab available on S800x.



## 60" BROOM

Clear debris and snow right down to the pavement. Bidirectional operation can be changed from the seat. (Optional cab available)



## GRASS CATCHER

A lightweight durable 3.75 bushel, fabric bag with hard plastic bottom attaches quickly.

# ACCESSORIES & ATTACHMENTS CHART

	S800x	S200xt	S150xt	S125xt	S50xt	SW35	SW25
Mulch Kit	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Trailer Hitch Kit	N/A	Optional	Optional	Optional	Optional	N/A	N/A
Light Kit	N/A	N/A	N/A	N/A	Optional	N/A	N/A
LED Light Kit	N/A	Optional	Optional	Optional	N/A	N/A	N/A
Armrests	Standard	Standard	Standard	Standard	Optional	N/A	N/A
Suspension Seat Insert	Optional	N/A	N/A	N/A	N/A	N/A	N/A
Suspension Seat	Optional	Optional	Optional	N/A	N/A	N/A	N/A
Premium Seat	Standard	Standard	Standard	Optional	N/A	N/A	N/A
Flat-Free Caster Tires	Optional	Optional	Optional	Optional	Optional	Standard	Standard
Professional Stripe Kit	Standard	Standard	Standard	Standard	Standard/Optional*	Optional	Optional†/N/A
Snowblower/Cab	Optional	N/A	N/A	N/A	N/A	N/A	N/A
60" Broom/Cab	Optional	N/A	N/A	N/A	N/A	N/A	N/A
Grass Catcher	N/A	N/A	N/A	N/A	Optional*/N/A	Optional†/N/A	Optional
Weight Kit	N/A	N/A	N/A	N/A	N/A	N/A	Optional

\*Optional on 36" models. †Optional on 48" and 52" models. ‡Optional on 48" models.

# MODEL SELECTION CHART

ENGINE		CUTTING WIDTH				
Gross HP/CC	Make	36"	48"	52"	61"	72"
15*/603	Kawasaki® FS541V	SW25	SW25, SW25cc			
18.5*/603	Kawasaki® FS600V	SW25cc	SW25, SW25cc			
19*/603	Kawasaki® FX600V	S50xt	S50xt			
20.5*/726	Kawasaki® FX651V		SW35, SW35cc	SW35, SW35cc		
23*/726	Kawasaki® FS691V			S125xt		
23.5*/726	Kawasaki® FX730V		S150xt	S150xt	SW35, SW35cc	
24*/726	Kawasaki® FS730V				S125xt	
25**/724	Briggs & Stratton® Commercial Series	S50xt	S50xt	S125xt		
25.5*/852	Kawasaki® FX801V				S200xt	
25.5*/726	Kawasaki® FS730V EFI				S125xt	
26**/810	Vanguard™ 810				S125xt, S200xt	
27**/810	Briggs & Stratton® Commercial Series				S125xt, S200xt	
28**/810	Vanguard™ 810 EFI			S150xt	S200xt	
28**/896	Vanguard™ BIG BLOCK™				S200xt	
31**/896	Vanguard™				S800x	S800x
37**/993	Vanguard™ BIG BLOCK™ EFI				S200xt	S200xt

\* All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki.

\*\* All power levels are stated gross horsepower at 3600 RPM per SAE J1940 as rated by Briggs & Stratton.



**SPECIFICATIONS**

**S800X**

**S200xt**

**S150xt**

**S125xt**

**S50xt**

**SW35**

**SW25**

**ENGINE**

Make (Gross Horsepower/Displacement)	Vanguard™ (31*/896cc)	Kawasaki® FX801V (25.5**/852cc), Vanguard™ 810 (26*/810cc), Briggs & Stratton® Commercial Series (27*/810cc), Vanguard™ 810 EFI (28*/810cc), Vanguard™ BIG BLOCK™ (28*/896cc), Vanguard™ BIG BLOCK™ EFI (37*/993cc)	Kawasaki® FX730V (23.5**/726cc), Vanguard™ 810 EFI (28*/810cc)	Kawasaki® FS691V (23**/726cc), Kawasaki® FS730V (24**/726cc), Kawasaki® FS730V EFI (25.5**/726cc), Briggs & Stratton® Commercial Series (25*/724cc and 27*/810cc)	Kawasaki® FX600V (19**/603cc), Briggs & Stratton® Commercial Series (25*/724cc)	Kawasaki® FX651V (20.5**/726cc), Kawasaki® FX730V (23.5**/726cc)	Kawasaki® FS541V (15**/603cc) or Kawasaki® FS600V (18.5**/603cc)
PTO	Electric	Electric	Electric	Electric	Electric	Electric	Electric
Cylinders	2	2	2	2	2	2	2
Starting	Electric	Electric	Electric	Electric	Electric	Electric	Manual/Electric
Fuel Capacity (TOTAL)	12 gallons	10 gallons / 5 gallons (S200XTB2761)	10 gallons	5.5 gallons	8 gallons / 4 gallons (S50XTB2536)	5 gallons	5 gallons

**MOWER**

Cutting Width (In.)	61, 72	61, 72	48, 52	52, 61	36, 48	48, 52, 61	36, 48
Cutting Height (In.)	1.5 - 5	1.5 - 6	1.5 - 5	1.5 - 5	1.5 - 4.5	1.5 - 4.75	1.5 - 4.5
Deck Construction	iCD™ Cutting System with professional lawn striper	iCD™ Cutting System with professional lawn striper	iCD™ Cutting System with professional lawn striper	iCD™ Cutting System with professional lawn striper	10-gauge, fabricated (36"), iCD™ Cutting System with professional lawn striper (48")	10-gauge, fabricated, double top deck, double reinforced side skirts, overlap welded corners	10-gauge, fabricated, double top deck, double reinforced side skirts, overlap welded corners
Spindles	Cast-iron, greaseable	Cast-iron, greaseable (61"), Hercules™ II, greaseable (72")	Cast-aluminum, greaseable (48"), Cast-iron, greaseable (52")	Cast-aluminum, greaseable	Cast-aluminum, greaseable	Cast-aluminum, greaseable	Cast-aluminum, greaseable
Belts	Single B-section Kevlar™ Corded Belts	Custom 5V belt with Kevlar™ Cords	Single 5V-section Kevlar™ Corded Belts	Single 5V-section Kevlar™ Corded Belts	Single B-section Kevlar™ Corded Belts	Single 5V-section Kevlar™ Corded Belts	Single B-section Kevlar™ Corded Belts

**CHASSIS**

Frame Rail	C-channel, 7-gauge	2" x 2", 7-gauge	1.5" x 2", 11-gauge	1.5" x 2", 11-gauge	1.5" x 2", 11-gauge	1.5" x 2", 11-gauge	1.5" x 2", 11-gauge
Bearings	Greaseable tapered caster yoke bearings			Greaseable tapered caster yoke bearings			
Finish	Powdura® Super Durable Powder Coat, a high gloss powder coat with excellent impact resistance and outstanding salt and U.V. protection			Powdura® Super Durable Powder Coat, a high gloss powder coat with excellent impact resistance and outstanding salt and U.V. protection			

**DRIVE SYSTEM**

Transmission	Dual pumps and wheel motors with 7" cooling fans	Commercial Hydro-Gear® ZT-5400 Powertrain® Transaxles with 9" cooling fans	Commercial Hydro-Gear® ZT-4400 Transaxles with 8.3" cooling fans	Commercial Hydro-Gear® ZT-3400® Transaxles with 7" cooling fans	Commercial Hydro-Gear® ZT-3100® Transaxles with 7" cooling fans	Commercial Hydro-Gear® ZT-3100® Transaxles with 7" cooling fans	Commercial Hydro-Gear® ZT-3100® Transaxles with 7" cooling fans
Drive Axles	1.25" Tapered	1.375" Tapered	1.375" Tapered	1.125" Tapered	1" Tapered	1" Tapered	1" Tapered
Drive Tires (in.)	24 x 12-12	24 x 12-12	24 x 9.5-12	22 x 11-10	20 x 7-10 (36"), 20 x 10-10 (48")	20 x 7 - 10 (48"), 20 x 8 - 10 (52", 61")	20 x 7-10
Caster Tires (in.)	13 x 6.5 (rear), 11 x 4 (front)	13 x 6.5-6	13 x 6.5-6	13 x 5-6	11 x 4-5	11 x 4 - 5 Flat-Free	9 x 3.5 - 4 Flat-Free

**GROUND SPEED**

Speeds-fwd. (mph)	0-10	0-10	0-10	0-10	0-8	0-7	0-6
Speeds-rev. (mph)	0-5	0-5	0-5	0-5	0-4	0-3	0-3

**DIMENSIONS**

Overall Length	115.5"	79" (61"), 82" (72")	78"	81"	69"	Standard: 78.75, CC™ :75" (48",52") Standard: 80.5", CC™ :76.75" (61")	Standard: 77.5", CC™ :73" (36"), Standard: 75.5", CC™ :71" (48")
Overall Width : deflector down / up	73" / 61.5" (61"), 88" / 74" (72")	76" / 63" (61"), 88" / 75" (72")	64" / 50" (48"), 68" / 54" (52")	67.5" / 54.5" (52"), 77" / 63.5" (61")	52" / 37" (36"), 64" / 49" (48")	62.5"/49.5" (48"), 67"/57" (52"), 76.5"/65" (61")	48.5"/37" (36"), 61"/49.5" (48")
Dry Weight (lbs.)	1514 (61"), 1677 (72")	1190 (61"), 1424 (72")	1107 (48"), 1141 (52")	1059 (52"), 1113 (61")	688 (36"), 724 (48")	809 (48"), 814 (52"), 888 (61")	632 (36"), 694 (48")

**OPERATOR CONTROL & COMFORT SYSTEMS**

Seat Package	Premium adjustable seat with armrests	Premium adjustable seat with armrests	Premium adjustable seat with armrests	Mid-back seat with armrests	Contour seat	N/A	N/A
Certified ROPS with retractable seat belt	Standard, 90° foldable	Standard, 165° foldable	Standard, 180° foldable	Standard, 180° foldable	N/A	N/A	N/A
Instrumentation	Hour meter	Hour meter, fuel level gauge	Hour meter, fuel level gauge	Hour meter, fuel level gauge	Hour meter, fuel level gauge	Hour meter, speed indicator	Hour meter, speed indicator
Safety Group / Controls	Seat actuated engine kill, blade, clutch safety switch, neutral and parking brake safety circuit / adjustable twin steering controls	Seat actuated engine kill, blade, clutch safety switch, neutral and parking brake safety circuit / adjustable twin steering controls	Seat actuated engine kill, blade, clutch safety switch, neutral and parking brake safety circuit / adjustable twin steering controls	Seat actuated engine kill, blade, clutch safety switch, neutral and parking brake safety circuit / adjustable twin steering controls	Seat actuated engine kill, blade, clutch safety switch, neutral and parking brake safety circuit / adjustable twin steering controls	Operator presence, centralized foot activated neutral pedals, neutral start safety circuit / cc™ (centralized controls) or standard controls	Operator presence, centralized foot activated neutral pedals, neutral start safety circuit / cc™ (centralized controls) or standard controls
Parking Brake	Disk type	Internal transaxle	Internal transaxle	Internal transaxle	Internal transaxle	Internal transaxle	Internal transaxle
Accessories	Collection system (61"), mulch kit, suspension seat, suspension seat insert, flat-free caster tires, snowblower/cab, broom/cab	Collection system (61"), mulch kit, trailer hitch kit, light kit, suspension seat, flat-free caster tires	Collection system, mulch kit, trailer hitch kit, light kit, suspension seat, flat-free caster tires	Collection system, mulch kit, trailer hitch kit, light kit, premium adjustable seat upgrade, flat-free caster tires	Collection system (48"), grass catcher (36"), mulch kit, trailer hitch kit, light kit, armrests, flat-free caster tires, professional stripe kit (36")	Grass catcher (48", 52"), mulch kit, professional stripe kit	Grass catcher, mulch kit, professional stripe kit (48"), weight kit

**WARRANTY**

Engine†	3-Year limited manufacturer's warranty			3-Year limited manufacturer's warranty			
Balance of Machine†	4-Year limited warranty (48 months) or 500 hours, whichever occurs first. Unlimited hours during the first 2 years (24 months). Belts, tires, brake pads, battery, blades: 90 days.			4-Year limited warranty (48 months) or 500 hours, whichever occurs first. Unlimited hours during the first 2 years (24 months). Belts, tires, brake pads, battery, blades: 90 days.		2-Year limited warranty commercial use, front-to-rear, parts & labor. Belts, tires, brake pads, battery, blades: 90 days.	

\* All power levels are stated gross horsepower at 3600 RPM per SAE J1940 as rated by Briggs & Stratton.  
\*\* All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki.

† See operator's manual or dealer for complete warranty details. Refer to engine operator's manual for engine warranty details.

\* All power levels are stated gross horsepower at 3600 RPM per SAE J1940 as rated by Briggs & Stratton.  
\*\* All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki.

† See operator's manual or dealer for complete warranty details. Refer to engine operator's manual for engine warranty details.





### **RIDE-ON 2+2 YEAR LIMITED WARRANTY\***

We know that each customer has different needs, and now we've got you covered with one simple warranty on all Snapper Pro® Ride-On Mowers, the 2+2 year limited warranty. Snapper Pro ride-on mowers, including all zero-turn series, and S800x models, are covered for 4 years (48 months) or 500 hours, whichever occurs first. During the first two-years (24 months), the mower is covered for unlimited hours. Belts, tires, brake pads, battery and blades are covered for 90 days. For engine warranty see engine operator's manual.

\*See operator's manual or dealer for complete warranty details.

**[www.SnapperPro.com](http://www.SnapperPro.com)**

HYDRO-GEAR® IS A TRADEMARK OF HYDRO-GEAR INC. AND IS USED UNDER LICENSE  
KAWASAKI® IS A REGISTERED TRADEMARK OF KAWASAKI MOTORS CORPORATION  
MARBAIN® IS A REGISTERED TRADEMARK OF THE FISHER-BARTON GROUP

BRIGGS & STRATTON: ALL POWER LEVELS ARE STATED GROSS HORSEPOWER AT 3600 RPM PER SAE J1940.

KAWASAKI: ONLY KAWASAKI CRITICAL POWER ENGINES LISTED IN THIS BROCHURE HAVE BEEN TESTED IN ACCORDANCE WITH SAE J1995, VERIFIED BY TÜV RHEINLAND GROUP, HORSEPOWER-RATED IN ACCORDANCE WITH SAE J2723, AND CERTIFIED BY SAE INTERNATIONAL. TORQUE RATINGS OF THESE ENGINES WERE NOT CERTIFIED BY SAE. ACTUAL POWER AND TORQUE OUTPUT WILL VARY DEPENDING ON NUMEROUS FACTORS, INCLUDING, BUT NOT LIMITED TO, THE OPERATING SPEED OF THE ENGINE IN APPLICATION, ENVIRONMENTAL CONDITIONS, MAINTENANCE, AND OTHER VARIABLES.

ACRES PER HOUR RATING SHOWN AT 80% EFFICIENCY TO REPRESENT TYPICAL MOWING CONDITIONS. MPH X WIDTH OF CUT / 124 = ACRES PER HOUR.

NOT ALL MODELS AVAILABLE IN CALIFORNIA. WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS, FEATURES AND PRICING WITHOUT NOTICE.

**BRIGGS&STRATTON PRODUCTS GROUP**

MUNNSVILLE, NY 13409 USA

800 933 6175

©2016 ALL RIGHTS RESERVED

PART # 2349\_SPR\_CAT\_0815

### **WALK-BEHIND 2 YEAR LIMITED WARRANTY\***

Walk-behind mowers are covered for two-years (24 months) for unlimited hours. Belts, tires, brake pads, battery and blades are covered for 90 days. For engine warranty see engine operator's manual.